## TASK CHAIR CASTORS



wheel movement is required

CASTOR NAME		DESCRIPTION	ESPECIALLY SUITABLE FOR
Standard castor For chairs with a		Made of high-durability nylon. Provides free-wheeling movement on most floor surfaces.	Carpet floors
traditional low-profile 5-star base		50mm diameter.	
Standard castor  For chairs with a		Made of high-durability nylon. Provides free-wheeling movement on most floor surfaces.	Carpet floors
high-profile 5-star base		60mm diameter.	
Brake castor		Wheels freely when the user's entire body weight is on the chair, locks when	Disabled users Laboratory situations
Also known as Friction Brake castor		there is no weight on it.  Prevents the chair rolling away from the user as they sit down.	
Soft Wheel castor		Polyurethane rim protects floor surfaces such as timber or soft vinyl.	Timber or soft vinyl floors Factory or other hard floors
		Also suitable on very hard smooth surfaces such as concrete, where standard castors roll too freely - the polyurethane rim provides greater friction.	, , , , , , , , , , , , , , , , , , , ,
Soft Wheel Brake castor		Polyurethane rim protects floor surfaces such as timber or soft vinyl.	Disabled users Laboratory situations Clinic situations Factory situations
		Wheels freely when user's entire body weight is on the chair, locks when there is no weight on it.  Stops the chair rolling away from the user as they sit down.	
Reverse Brake castor		Wheels freely when there is no weight on the chair, locks when the user sits down.	Surgical or clinic situations
		The reverse brake function can be turned on or off by the lever at the back of the castor.	
Manual Brake castor		Brake feature is activated manually by a little lever on the front of each castor.	Disabled users
		by a tittle tever on the nont of each castor.	Situations where movemen is only sometimes required
Large castor		Large 60mm diameter.	Large users
		Allows the chair to wheel more freely than the smaller 50mm standard castor.	Disabled users
Glide		A flat-based foot that provides no movement.	Factory or machinery-use, or any situation where no
		0111 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	wheel movement is required

Glide height 40mm.

A chair with glides will sit 20mm or 30mm lower than with standard castors.